

SQUARE METAL POST


NOTES:

SIGN POST:

- ① SIGN POST SHALL BE 2"x2" SQUARE STEEL POSTS, MINIMUM 14 GAUGE, WITH 7/16" DIE-PUNCHED KNOCKOUTS ON 1" CENTERS FULL LENGTH FOUR SIDES COMPLYING W/ ASTM SPEC A653 AND BE HOT DIPPED GALVANIZED.
- ② ANCHOR SHALL BE 2.25"x2.25" OD SQUARE STEEL, MINIMUM 14 GAUGE WITH 7/16" DIE PUNCHED KNOCKOUTS ON 1" CENTER COMPLYING WITH ASTM SPEC. A653 AND BE HOT DIPPED GALVANIZED. ANCHOR SHALL HAVE MINIMUM OF 3 HOLES ABOVE GRADE.
- ③ ANCHOR SHALL HAVE TAPE INSTALLED ON BOTTOM AS WELL AS ALL SIDES TO KEEP INSIDE CLEAR OF ALL MATERIAL.
- ④ INSTALL TWO DRIVE RIVETS
ZUMAR INDUSTRIES #TL3806 OR EQUIVALENT
- ⑤ INSTALL TWO CORNER BOLTS AND NUTS
ZUMAR INDUSTRIES #TL070 OR EQUIVALENT
- ⑥ 4"x4" WOODEN PRESSURE TREATED POST MAY BE USED WHEN POST IS MORE THAN 10' FROM EDGE OF TRAVEL LANE (OR APPROVED BY ENGINEER).

SIGN INSTALLATION:

SEE TRAFFIC STREET SIGN DETAIL TR-575 FOR GUIDANCE ON SIGN INSTALLATIONS.



CITY OF EDMONDS
PUBLIC WORKS
DEPARTMENT

**SIGN POST INSTALLATION
IN NON-SIDEWALK AREA**

APPROVED BY: R. ENGLISH

REVISION DATE
OCTOBER 2018

STANDARD
DETAIL
TR-571