


CONSTRUCTION REQUIREMENT:

1. 5/8 X 12 GALV. CARRIAGE BOLT WITH HEX NUT POST BOLT WASHER IN 3/4" HOLE. USE TWO BOLTS AT EACH RAIL TO POST CONNECTION.
2. INSTALL 3 YELLOW 3" DIAMETER CENTER MOUNT REFLECTORS (TYPE 2 OBJECT MARKER) ON END GUARDRAIL POST OR AN APPROVED MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) OBJECT MARKER.
3. SPACE TIMBER POSTS (6" X 8" X 6') 6' ON CENTER
4. ALL TIMBER GUARDRAIL INSTALLATIONS MUST BE APPROVED BY THE CITY ENGINEER. TIMBER GUARDRAILS SHALL ONLY BE INSTALLED ALONG LOW VOLUME RESIDENTIAL STREETS. TRADITIONAL BEAM GUARDRAIL SHALL BE INSTALLED WHEN WARRANTED ON HIGH VOLUME ROADWAYS SUCH AS COLLECTOR AND ARTERIAL STREETS, AS DETERMINED BY THE CITY TRAFFIC ENGINEER.



CITY OF EDMONDS

REVISIONS		STANDARD DETAIL		
APPROVED BY	DATE			
		TIMBER GUARDRAIL DETAIL		
DATE	03/24/05	SCALE	NTS	DWG NO. E 8.13